

Truck Champ

**INSTALLATION INSTRUCTIONS
OVAL SIDE BAR
NISSAN TITAN CREW CAB\EXT. CAB 05-07
PART # 197242, 197243**

PARTS LIST

- | | |
|-------------------------------|-----------------------------------|
| (1) Side bar – passenger side | (12) 3/8"x1" button head bolts |
| (1) Side Bar – Driver side | (12) 3/8" sae black flat washers |
| (2) Front mount brackets | (12) 3/8" lock washer |
| (2) Middle mount brackets | (6) 8mm 1.25 x 25mm zinc hex bolt |
| (2) Rear mount brackets | (6) 8mm 1.25 zinc nut |
| (12) 8mm black flat washers | |

PROCEDURE

- 1 Begin installation by working on driver side of the vehicle starting at the front of the inner rocker panel.
- 2 Located on the inside as well as the bottom inner of the rocker panel you will see one thread hole and one thread stud for each mounting bracket refer to diagram 1. (Note all brackets are labeled)
- 3 Install mounting brackets to inner rocker panel using 8mm 1.25 x 25 mm bolts plus 8mm nuts and washers as shown in diagram 2. Hand tighten only.
- 4 Attach side bar to brackets using the 3/8" button head bolts and washers. Align the side bar with the vehicle body, then tighten & torque all fasteners to 30ft-lbs. Repeat steps for passenger side to complete installation.

DIAGRAM 1. DIAGRAM 2.



Finish Protection- Our product have a high finish that must be maintained such as any other high finish product on the vehicle. Protect the finish with a non-abrasive automotive wax. The use of soap, polish, or wax that contains abrasives is detrimental, as the compounds scratch the finish and open it to corrosion.

DISCLAIMER- Buyer assumes all risk and liability whatsoever from the installation and use of our products. Our products are sold as decorative accessories and should not be relied upon as protection for the vehicle or occupants in the event of a collision or roll over. The Manufacturer assumes no liability for injury, loss, incidental or consequential damages in the event of a collision or rollover.